

Technische specificaties

Maximale werkdruk	6 bar
Gereedschap	Slijptol
Merk	Al-ko, Avola, Dust-Best, Evotec, Ghibli, Heylo, Honeywell, Kemper
Zaaghoogte	30 mm , 0-90 mm , 0-105 mm , 135 mm , 0-135 mm , 153 mm , 145 mm , 0-145 mm , 170 mm , 0-170 mm , 113/164/245 mm
Onderdruk	12500 Pa , 100 Pa , 150 Pa , 190 Pa , 250 Pa , 360/625 Pa , 287 Pa , 600 Pa , 350 Pa , 370 Pa , 550 Pa , 25000 Pa , 24000 Pa , 24500 Pa , 21000 Pa , 19600 Pa , 50 Pa , 2400 Pa , 70 Pa , 500 Pa , 19600 Pa , 450 Pa , 450 Pa , 450 (bij 60 Hz) Pa , 425 Pa , 410 Pa , 280 Pa , 1000 Pa , 720 Pa , 537 Pa , 400 Pa , 1750 Pa , 1600 Pa , 1780 Pa , 2700 Pa , 620 Pa , 1800 Pa , 272 Pa , 429 Pa , 744 Pa , 314 Pa , 195 Pa , 2950 Pa , 29500 Pa , 254 Pa
Voorfilter	0,19 m ² , 0,35 m ² , 0,8 m ² , 0,3 m ² , 1,4 m ² , 1,87 m ²
Voorfilter klasse	M klasse
Hoofdfilter	H m ² , 0,8 m ² , 9,2 m ² , 1,1 m ² , 2,2 m ² , 4,4 m ² , 9,8 m ² , 1,6 m ² , 3 m ² , 9,0 m ² , 3 m ² , 2 m ² , 2,6 m ² , 13 m ² , 17 m ²
Hoofdfilter klasse	H klasse , H13 klasse
Max. slanglengte	15 mtr , 45 mtr , 3x10 mtr , 10 mtr , 20 mtr

Luchtdebiet	4200 m³/h, 6500 m³/h, 2050 m³/h, 8900 m³/h, 12600 m³/h, 11000 m³/h, 11650/16100 m³/h, 1100 m³/h, 1250 m³/h, 605 m³/h, 90 m³/h, 710 m³/h, 1410 m³/h, 1550 m³/h, 350 m³/h, 750 m³/h, 343 m³/h, 2930/3880 m³/h, 7560 m³/h, 1856/1996/2091 m³/h, 850 m³/h, 3600 m³/h, 194 m³/h, 104 m³/h, 137 m³/h, 209 m³/h, 191 m³/h, 180 m³/h, 600 m³/h, 580 m³/h, 1150 m³/h, 2400 m³/h, 4250 m³/h, 540 m³/h, 1392 m³/h, 1270 m³/h, 140 m³/h, 1050 m³/h, 550 m³/h, 250 m³/h, 300 m³/h, 500 m³/h, 650 m³/h, max. 240 m³/h, 3800 m³/h, 12480 m³/h, 2263/2645/2920 m³/h, 1190 m³/h, 1400 m³/h, 3200 m³/h, 3084 m³/h, 382 m³/h, 4141 m³/h, 3680 m³/h, 5900 m³/h, 1650 m³/h, 1350 m³/h, 865 m³/h, 2500 m³/h, 360 m³/h, 1200 m³/h, 1500 m³/h, 1183 m³/h, 2690 m³/h, 4954 m³/h, 4954 m³/h, 10550 m³/h, 2093 m³/h, 1195 m³/h, 155 m³/h, 9420 m³/h, 11156 m³/h, 12767 m³/h, 10567 m³/h, 330 m³/h, 198 m³/h, 188 m³/h, 148 m³/h, 224 m³/h, 950 m³/h, 2 x 700 m³/h
Aansluitkoppeling	50 ø mm , 38 ø mm , 90 ø mm , 305 ø mm , 420 ø mm , 200 ø mm , 125 ø mm , 2x 205 ø mm , 205 ø mm , 38/50 ø mm , 550 ø mm , 3x 102 ø mm , 520 ø mm , 405 ø mm , 140 ø mm , 160 ø mm , 100 ø mm , 125/80 ø mm
Verbruik	1/2 kg/h , 1,4-2,9 kg/h , 3,04 olie kg/h , 2,5 kg/h , 4,7 kg/h , 6,8 kg/h , 10,1 kg/h , 11,9/13,1 kg/h , 14 kg/h , 13,1/19,0 kg/h , 2,7 kg/h

Diameter zaagblad	315 Ø mm , 350 Ø mm , 400 Ø mm , 450 Ø mm , 500 Ø mm , 180 Ø mm , 150 Ø mm , 125 Ø mm , 250 Ø mm
Asmaat zaagblad	30 Ø mm , 650 Ø mm , 40 Ø mm
Afmetingen lengte	956 mm , 1110 mm , 1150 mm , 1460 mm , 1450 mm , 450 mm , 410 mm , 500 mm , 425 mm , 590 mm , 510 mm , 620 mm , 1155 mm , 525 mm , 670 mm , 1000 mm , 800 mm , 500 mm , 470 mm , 1447 mm , 1623 mm , 1674 mm , 1878 mm , 2000 mm , 2191 mm , 2298 mm , 570 mm , 730 mm , 466 mm , 580 mm , 1215 mm , 480 mm , 1100 mm , 406 mm , 400 mm , 280 mm , 330 mm , 385 mm , 1075 mm , 145 mm , 680-830 mm , 7600 mm , 462 mm , 480 mm , 225 mm , 370 mm , 340 mm , 460 mm , 40 mm , 520 mm , 655 mm , 610 mm , 505 mm , 710 mm , 420 mm , 2991 mm , 770 mm , 650 mm , 350 mm , 390 mm , 1060 mm , 615 mm , 1090 mm , 896 mm , 1200 mm , 1250 mm , 630 mm , 1500 mm , 4800 mm , 4400 mm , 411 mm , 495 mm , 765 mm , 57 mm , 500 mm , 5000 mm , 1900 mm
Nominaal vermogen	2200 kW , 1100 kW , 50 kW , 76 kW , 29 kW , 110 kW , 133/151 kW , 153 kW , 148/218 kW , 36 kW , 3/6/9 kW , 18 kW , 1/2 kW , 4,5/9 kW , 15-30 kW , 15/30 kW , 22/45 kW , 1,5/3 kW , 6/12/18 kW , 1900 kW , 2900 kW , 1,9 kW , 2,9 kW

Afmetingen breedte 430 mm , 575 mm , 750 mm , 750 mm , 1440 mm , 500 mm , 410 mm , 440 mm , 585 mm , 580 mm , 565 mm , 655 mm , 770 mm , 820 mm , 715 mm , 510 mm , 545 mm , 500 mm , 690 mm , 795 mm , 875 mm , 971 mm , 1002 mm , 1294 mm , 414 mm , 168 mm , 322 mm , 285 mm , 510 mm , 800 mm , 381 mm , 530 mm , 480 mm , 250 mm , 305 mm , 385 mm , 665 mm , 435 mm , 240 mm , 310 mm , 320 mm , 372 mm , 520 mm , 650 mm , 1200 mm , 400 mm , 640 mm , 457 mm , 420 mm , 460 mm , 450 mm , 2438 mm , 670 mm , 525 mm , 550 mm , 860 mm , 515 mm , 581 mm , 1000 mm , 630 mm

Zuigvermogen 330 W, 353 W, 285 W, 425 W, 230 W, 410 W, 540 W, 530 W, 780 W

Stekker 16 model , Schuko model , CEE 516 model

Zekering 16 A (traag) , 32 A (traag) , 64 A (traag) , 20 A (traag)

Spanning 4200 V , 2700 V , 230 V , 400 V , 24 V DC V , 230/400 V

Afmetingen hoogte 450 mm , 1250 mm , 1240 mm , 570 mm , 1270 mm , 795 mm , 815 mm , 1000 mm , 890 mm , 900 mm , 920 mm , 1180 mm , 485 mm , 1140 mm , 1320 mm , 1070 mm , 1600 mm , 1150 mm , 1495 mm , 850 mm , 790 mm , 830 mm , 822 mm , 1082 mm , 1300 mm , 1410 mm , 1510 mm , 1709 mm , 482 mm , 414 mm , 420 mm , 428 mm , 670 mm , 610 mm , 2100 mm , 406 mm , 580 mm , 490 mm , 300 mm , 355 mm , 225 mm ,

Afmetingen kniphoogte	650 mm
Afmetingen knipbreedte	310 mm
Afmetingen knipkracht	26 ton
Tankinhoud	35 ltr , 5 ltr , 90 ltr , 16 (container) / 14 (stofzak) ltr , 25/50 ltr , 42 ltr , 30 ltr , 35/70 ltr , 70 ltr , 58+30 ltr , 14/22 ltr , 28/43 ltr , 185 ltr , 42/58 ltr , 200 ltr , 50 (bruto) - 35 (netto) ltr , 100 ltr , 175 ltr , 65 ltr , Big bag 1100 L, voorafscheider 60 ltr , Big bag 1100 ltr, voorafscheider 60 ltr , 80 ltr , 56 ltr , 19 ltr , 25 ltr , 60 ltr , 60/40 ltr , 77/58 ltr , 20 ltr , 40 ltr , 5,3 ltr , 6 ltr , 18 ltr , 8 ltr , 9 ltr
Geluidsdruk onbelast	59 dB(A) , 58 dB(A) , 72 dB(A) , 67 dB(A) , 52 dB(A) , 59/68,1 dB(A) , 73 dB(A) , 43 dB(A) , 61 dB(A) , 85 dB(A) , 68 dB(A) , 81 dB(A) , 65 dB(A) , 83 dB(A) , 82,4 dB(A) , 77,3 dB(A) , 95 dB(A) , 84,4 dB(A) , 79,3 dB(A) , 79,5 dB(A) , 70 dB(A) , 62,5 dB(A) , 66 dB(A) , 77 dB(A) , 75 dB(A) , <70 dB(A) , 49 dB(A) , 72 dB(A) , 67/71 dB(A) , 89 dB(A) , 69 dB(A) , 45 dB(A) , 52 dB(A) , 39 dB(A) , 41 dB(A) , 51 dB(A) , 78 dB(A) , 90 dB(A) , 84 dB(A) , 66,5 dB(A) , 63/51 dB(A)

Gewicht	69 kg , 44 kg , 36 kg , 15 kg , 7,3 kg , 20 kg , 3,2 kg , 4,6 kg , 19,9 kg , 17 kg , , 77 kg , 83 kg , 126 kg , 156 kg , 222 kg , 121 kg , 135 kg , 170 kg , 140 kg , 175 kg , 460 kg , 59 kg , 1,8 kg , 2,9 kg , 3,7 kg , 6,1 kg , 5 kg , 10 kg , 22 kg , 12 kg , 35 kg , 33 kg , 27 kg , 52 kg , 13,5 kg , 30 kg , 46 kg , 48 kg , 40 kg , 49 kg , 118 kg , 45 kg , 65 kg , 37 kg , 85 kg , 190 kg , 225 kg , 290 kg , 340 kg , 480 kg , 18,5 kg , 20,5 kg , 22 kg , 14,5 kg , 15 kg , 16,5 kg , 16,3 kg , 195 kg , 25 kg , 8 kg , 35 kg , 11,5 kg , 4,8 kg , 39 kg , 20 kg , 23 kg , 49 kg , 9,7 kg , 17,5 kg , 16 kg , 54 kg , 9,5 kg , 8,2 kg , 24 kg , 2,0 kg , 2,6 kg , 3,5 kg , 4,5 kg , 4,0 kg , 8,0 kg , 8,4 kg , 3,8 kg , 5,5 kg , 6,0 kg , 7,4 kg , 1000 kg , 1675 (incl. K120) kg , 2685 (compleet) kg , 2685 (totaal gewicht) kg , 2750 kg , 2750 (totaal gewicht) kg , 41 kg , 14 kg , 44,5 kg
A1test	10
A2test	10, 20
Standaard slanglengte	10 mtr, 20 mtr, 4 mtr, 2,75 mtr, 5 mtr, 3,10 mtr, 3,10 mtr
IP-klasse	55, 65, 44, 54, 21
ATEX Zone	22, 3, 1 en 21
Capaciteit oppervlakte	60 m², 60 m², 58 m², 110 m², 110 m², 130 m², 100 m²
Schuinverstelling	0-45°, 90°-30°
Maximaal vermogen	6,5

Type	270 Power, AS 27 IK HD, AS 27 IK, AS 27 P, AS 40 KS M, AS 400 IK HD, AS 400 IK, AS 59 IK HD, AS 59 IK, AS 60 IK HD, AS 60 IK, Power D 12, Power InDust 60 TP Z22, Power InDust 60 TP M, Power InDust AX 20 SP Z22, Power InDust AX 20 TP Z22, Power InDust AX 60 TP Z22, Power Tool Pro FD 22 P EL, Power Tool Pro FD 50 P EL M, Power Tool Pro FD 50 P Combi M, MRV-8 Poly, Superpro 700, Superpro Battery 700, Superpro Micron 700 automat, Superpro Micron 700, PRO BATTERY, 1200, 1800H Power, 1800H Power, 20, 2-58 DUO, 2000 (2200W), 2000 (3300W), 200H, 200H Power, 200H Power, 2600 (2200W), 2600 (3300W), 35, C-10 EX (4W), Automatic X7, F-3400, CF- 502P, CF-502A, Safe-Change, C120, 600 NPU, 550, 520, 500, 5-58 DUO K- A, 370, 350, 3400 (3300W), 3400 (2200W), 330, 300, EW 18-e, AT 20, AT 30, BT 60, Compact 1500 EX, DE 10, DE 2 XL, DE 20, DE 20 S, DE 20 SH, DE 20 SH-U, DE 3 XL, DE 3 XL PRO, DE 30, DE 9 XL, DG 25 S, DG 45 A, DG 45 S, DS 30 T, DT 550, DT 650, DT 750, DT 760, DT 860, DT 950, DT 960, FD 360°, FD 4000, HV 2000, IRW 200, IRW 200 PRO, IRW 500, IRW 500 PRO, K 120, K 120 R, K 160, K 160 R, K 30 T, K 50, K 80, KT 20, PowerFilter 1000, PowerFilter 3500, PowerFilter 1400, Powervent 12000, Powervent 1500
Doorvoerbreedte	930 mm

Vermogen	54 kW , 83 kW , 32 kW , 120 kW , 141/161 kW , 168 kW , 155/234 kW , 15/30 kW , 22/45 kW , 1/2 kW , 9 kW , 6/12/18 kW , 9/18/27 kW , 4,5/9 kW , 0,76 kW , 0,92 kW , 0,69 kW , 0,19 kW , 0,27 kW , 0,75 kW , 0,55 kW , 0,56 kW , 0,085 kW , 0,13 kW , 0,25 kW , 0,49 kW , 2700 kW , 3100 kW , 4000 kW , 3200 kW , 4200 kW , 5200 kW , 6400 kW , 0,85 kW , 1,75 kW , 1,55 kW , 0,4 kW , 1 kW , 1,1 kW , 1,2 kW , 2,4 kW , 0,75 x 2 kW , 1,8 kW , 2,2 kW , 3,3 kW , 303 kW , 1,55 kW , 1,5 kW , 3,1 kW , 4,0 kW , 5,2 kW , 6,4 kW , 4,2 kW , 2,7 kW , 3,2 kW , 2,4 kW , 0,6 kW , 0,33 kW , 0,55 kW , 0,58 kW , 0,95 kW , 0,2 kW , 0,5 kW , 0,62 kW , 3,7 kW , 0,124 kW , 0,29 kW , 0,175 kW , 0,48 kW , 0,89 kW , 1,75 kW
CADR-waarde	800 m ³ /h, 350 m ³ /h, 250
Werkhoogte	850 mm
Overdruk	6 bar
Toerental	CEE 516 Omw/min , 6800 Omw/min , 2000-7000 Omw/min , 1700-6800 Omw/min , 9500 Omw/min , 1900- 9500 Omw/min , 2700-9500 Omw/min , 6600 Omw/min , 3000 Omw/min , 800-3600 Omw/min , 2700-6800 Omw/min
Maximale uitblaastemperatuur	165 °C

EAN code

4052228043211, 4052228000382,
4052228000443, 4052228000450,
4052228029338, 4052228029345,
4052228029352, 4052228029369,
4052228026535, 4052228014839,
4052228037562, 4052228027020,
4052228022773, 4052228023787,
4052228022780, 4052228030075,
4052228029383, 4052228033618,
4052228000221, 4052228039634,
4052228037357, 4052228043174,
4052228037715, 4052228039627,
4052228038125, 4052228038033,
4052228039641, 4052228022179,
4052228022186, 4052228027068,
4052228027075, 4052228002102,
4052228002133, 4052228002171,
4052228002195, 4052228002201,
4052228002225, 4052228002249,
4052228002263, 4052228002270,
4052228002287, 4052228000184,
4052228025477, 4052228027594,
4052228027884, 4052228031447,
4052228031454, 4052228034240,
4052228021066, 4052228026122,
4052228028270, 4052228027167,
4052228027174, 4052228027181,
4052228027129, 4052228027136,
4052228027143, 4052228033625,
4052228029499, 4052228029307,
4052228029314, 4052228029321,
4052228033281, 4052228036268,
4052228038620, 4052228027150,
4052228018943, 4052228002638,
4052228002652, 4052228002669,
4052228002690, 4052228013276,
4052228013269, 4052228013290,
4052228017540, 4052228016369,

Optioneel

2BEST, Product & Innovatie
Industrieweg 9
7141 DD Groenlo

Tel: +31 (0) 544-488770
info@2best.nl
2best.nl

Op al onze gesloten overeenkomsten zijn de algemene in- en verkoopvoorwaarden van 2BEST van toepassing, te vinden op [2BEST.nl](https://2best.nl)