

Technische specificaties

Zuigvermogen	330 W, 353 W, 285 W, 425 W, 230 W, 410 W, 540 W, 530 W, 780 W
Standaard slanglengte	10 mtr, 20 mtr, 4 mtr, 2,75 mtr, 5 mtr, 3,10 mtr, 3,10 mtr
Schuinverstelling	0-45°, 90°-30°
Afmetingen lengte	956 mm , 1110 mm , 1150 mm , 1460 mm , 1450 mm , 450 mm , 410 mm , 500 mm , 425 mm , 590 mm , 510 mm , 620 mm , 1155 mm , 525 mm , 670 mm , 1000 mm , 800 mm , 500 mm , 470 mm , 1447 mm , 1623 mm , 1674 mm , 1878 mm , 2000 mm , 2191 mm , 2298 mm , 570 mm , 730 mm , 466 mm , 580 mm , 1215 mm , 480 mm , 1100 mm , 406 mm , 400 mm , 280 mm , 330 mm , 385 mm , 1075 mm , 145 mm , 680-830 mm , 7600 mm , 462 mm , 480 mm , 225 mm , 370 mm , 340 mm , 460 mm , 40 mm , 520 mm , 655 mm , 610 mm , 505 mm , 710 mm , 420 mm , 2991 mm , 770 mm , 650 mm , 350 mm , 390 mm , 1060 mm , 615 mm , 1090 mm
A2test	10, 20
Maximaal vermogen	6,5
Geluidsdruk onbelast	59 dB(A) , 58 dB(A) , 72 dB(A) , 67 dB(A) , 52 dB(A) , 59/68,1 dB(A) , 73 dB(A) , 43 dB(A) , 61 dB(A) , 85 dB(A) , 68 dB(A) , 81 dB(A) , 65 dB(A) , 83 dB(A) , 82,4 dB(A) , 77,3 dB(A) , 95 dB(A) , 84,4 dB(A) , 79,3 dB(A) , 79,5 dB(A) , 70 dB(A) , 62,5 dB(A) , 66 dB(A) , 77 dB(A) , 75 dB(A) , <70 dB(A) , 49 dB(A) , 72 dB(A) , 67/71 dB(A) , 89 dB(A) , 69 dB(A) , 45 dB(A) , 52 dB(A) , 39 dB(A) , 41 dB(A) , 51 dB(A)

Type	270 Power, AS 27 IK HD, AS 27 IK, AS 27 P, AS 40 KS M, AS 400 IK HD, AS 400 IK, AS 59 IK HD, AS 59 IK, AS 60 IK HD, AS 60 IK, Power D 12, Power InDust 60 TP Z22, Power InDust 60 TP M, Power InDust AX 20 SP Z22, Power InDust AX 20 TP Z22, Power InDust AX 60 TP Z22, Power Tool Pro FD 22 P EL, Power Tool Pro FD 50 P EL M, Power Tool Pro FD 50 P Combi M, MRV-8 Poly, Superpro 700, Superpro Battery 700, Superpro Micron 700 automat, Superpro Micron 700, PRO P58, 1200, 1800H Power, 1800H Power, 20, 2-58 DUO, 2000 (2200W), 2000 (3300W), 200H, 200H Power, 200H Power, 2600 (2200W), 2600 (3300W), 35, C-10 EX (4W), Automatic X7, F-3400, CF-502P, CF-502A, Safe-Change, C120, 600 NPU, 550, 520, 500, 5-58 DUO K-A, 370, 350, 3400 (3300W), 3400 (2200W), 330, 300, EW 18-e, AT 20, AT 30, BT 60, Compact 1500 EX, DE 10, DE 2 XL, DE 20, DE 20 S, DE 20 SH, DE 20 SH-U, DE 3 XL, DE 3 XL PRO, DE 30, DE 9 XL, DG 25 S, DG 45 A, DG 45 S, DS 30 T, DT 550, DT 650, DT 750, DT 760, DT 860, DT 950
Nominaal vermogen	2200 kW , 1100 kW , 50 kW , 76 kW , 29 kW , 110 kW , 133/151 kW , 153 kW , 148/218 kW , 36 kW , 3/6/9 kW , 18 kW , 1/2 kW , 4,5/9 kW , 15-30 kW , 15/30 kW , 22/45 kW , 1,5/3 kW , 6/12/18 kW , 1900 kW
Tankinhoud	35 ltr , 5 ltr , 90 ltr , 16 (container) / 14 (stofzak) ltr , 25/50 ltr , 42 ltr , 30 ltr , 35/70 ltr , 70 ltr , 58+30 ltr , 14/22 ltr , 28/43 ltr , 185 ltr , 42/58 ltr , 200 ltr , 50 (bruto) - 35 (netto) ltr , 100 ltr , 175 ltr ,

Afmetingen knipbreedte	310 mm
Afmetingen kniphooft	650 mm
Onderdruk	12500 Pa , 100 Pa , 150 Pa , 190 Pa , 250 Pa , 360/625 Pa , 287 Pa , 600 Pa , 350 Pa , 370 Pa , 550 Pa , 25000 Pa , 24000 Pa , 24500 Pa , 21000 Pa , 19600 Pa , 50 Pa , 2400 Pa , 70 Pa , 500 Pa , 19600 Pa , 450 Pa , 450 Pa , 450 (bij 60 Hz) Pa , 425 Pa , 410 Pa , 280 Pa , 1000 Pa , 720 Pa , 537 Pa , 400 Pa , 1750 Pa , 1600 Pa , 1780 Pa , 2700 Pa , 620 Pa
Kabellengte	4 mtr , 8 mtr , 10 mtr , 15 mtr , 4,5 mtr , 18 mtr , 12 mtr
Luchtdebiet	4200 m ³ /h, 6500 m ³ /h, 2050 m ³ /h, 8900 m ³ /h, 12600 m ³ /h, 11000 m ³ /h, 11650/16100 m ³ /h, 1100 m ³ /h, 1250 m ³ /h, 605 m ³ /h, 90 m ³ /h, 710 m ³ /h, 1410 m ³ /h, 1550 m ³ /h, 350 m ³ /h, 750 m ³ /h, 343 m ³ /h, 2930/3880 m ³ /h, 7560 m ³ /h, 1856/1996/2091 m ³ /h, 850 m ³ /h, 3600 m ³ /h, 194 m ³ /h, 104 m ³ /h, 137 m ³ /h, 209 m ³ /h, 191 m ³ /h, 180 m ³ /h, 600 m ³ /h, 580 m ³ /h, 1150 m ³ /h, 2400 m ³ /h, 4250 m ³ /h, 540 m ³ /h, 1392 m ³ /h, 1270 m ³ /h, 140 m ³ /h, 1050 m ³ /h, 550 m ³ /h, 250 m ³ /h, 300 m ³ /h, 500 m ³ /h, 650 m ³ /h, max. 240 m ³ /h, 3800 m ³ /h, 12480 m ³ /h, 2263/2645/2920 m ³ /h, 1190 m ³ /h, 1400 m ³ /h, 3200 m ³ /h, 3084 m ³ /h, 382 m ³ /h, 4141 m ³ /h, 3680 m ³ /h, 5900 m ³ /h, 1650 m ³ /h, 1350 m ³ /h, 865 m ³ /h, 2500 m ³ /h, 360 m ³ /h, 1200 m ³ /h, 1500 m ³ /h, 1183 m ³ /h, 2690 m ³ /h, 4954 m ³ /h, 4954 m ³ /h
Aansluitkoppeling	50 ø mm , 38 ø mm , 90 ø mm , 305 ø mm , 420 ø mm , 200 ø mm , 125 ø mm

Gewicht 69 kg , 44 kg , 36 kg , 15 kg , 7,3 kg , 20 kg , 3,2 kg , 4,6 kg , 19,9 kg , 17 kg , 77 kg , 83 kg , 126 kg , 156 kg , 224 kg , 121 kg , 135 kg , 170 kg , 140 kg , 175 kg , 460 kg , 59 kg , 1,8 kg , 2,9 kg , 3,7 kg , 6,1 kg , 5 kg , 10 kg , 22 kg , 12 kg , 35 kg , 33 kg , 27 kg , 52 kg , 13,5 kg , 30 kg , 46 kg , 48 kg , 40 kg , 49 kg , 118 kg , 45 kg , 65 kg , 37 kg , 85 kg , 190 kg , 225 kg , 290 kg , 340 kg , 480 kg , 18,5 kg , 20,5 kg , 22 kg , 14,5 kg , 15 kg , 16,5 kg , 16,3 kg , 195 kg , 25 kg , 8 kg , 35 kg , 11,5 kg , 4,8 kg , 39 kg , 20 kg , 23 kg , 49 kg , 9,7 kg , 17,5 kg , 16 kg , 54 kg , 9,5 kg , 8,2 kg , 24 kg , 2,0 kg , 2,6 kg , 3,5 kg , 4,5 kg

Max. slanglengte 15 mtr , 45 mtr , 3x10 mtr , 10 mtr , 20 mtr

Afmetingen 450 mm , 1250 mm , 1240 mm , 570 mm , 1270 mm , 795 mm , 815 mm , 1000 mm , 890 mm , 900 mm , 920 mm , 1180 mm , 485 mm , 1140 mm , 1320 mm , 1070 mm , 1600 mm , 1150 mm , 1495 mm , 850 mm , 790 mm , 830 mm , 822 mm , 1082 mm , 1300 mm , 1410 mm , 1510 mm , 1709 mm , 482 mm , 414 mm , 420 mm , 428 mm , 670 mm , 610 mm , 2100 mm , 406 mm , 580 mm , 490 mm , 300 mm , 355 mm , 225 mm , 615 mm , 850 mm , 625 mm , 980 mm , 313 mm , 690 mm , 660 mm , 735 mm , 380 mm , 560 mm , 530 mm , 720 mm , 480 mm , 457 mm , 229 mm , 445 mm , 1010 mm , 510 mm , 2591 mm , 500 mm , 1200 mm

IP-klasse 55, 65, 44

Hoofdfilter klasse H klasse , H13 klasse

Afmetingen breedte	430 mm , 575 mm , 750 mm , 810 mm , 1440 mm , 500 mm , 410 mm , 440 mm , 585 mm , 580 mm , 565 mm , 655 mm , 770 mm , 820 mm , 715 mm , 510 mm , 545 mm , 500 mm , 690 mm , 795 mm , 875 mm , 971 mm , 1002 mm , 1294 mm , 414 mm , 168 mm , 322 mm , 285 mm , 510 mm , 800 mm , 381 mm , 530 mm , 480 mm , 250 mm , 305 mm , 385 mm , 665 mm , 435 mm , 240 mm , 310 mm , 320 mm , 372 mm , 520 mm , 650 mm , 1200 mm , 400 mm , 640 mm , 457 mm , 420 mm , 460 mm , 450 mm , 2438 mm , 670 mm
A1test	10
Extra wcd	2000 W , 2500 W
Voorfilter	0,19 m ² , 0,35 m ² , 0,8 m ² , 0,3 m ² , 1,4 m ²
Frequentie	50 Hz
Nominale cap.	48 l/24h , 70 l/24h , 58 l/24h , 3/6/9 l/24h , 55 l/24h , 16 l/24h , 28 l/24h , 33 l/24h , 44 l/24h , 62 l/24h
Capaciteit oppervlakte	60 m ² , 60 m ² , 58 m ² , 110 m ² , 110 m ² , 130 m ² , 100 m ²
Verbruik	1/2 kg/h , 1,4-2,9 kg/h , 3,04 olie kg/h , 2,5 kg/h , 4,7 kg/h , 6,8 kg/h , 10,1 kg/h , 11,9/13,1 kg/h , 14 kg/h , 13,1/19,0 kg/h
ATEX Zone	22
Hoofdfilter	H m ² , 0,8 m ² , 9,2 m ² , 1,1 m ² , 2,2 m ² , 4,4 m ² , 9,8 m ² , 1,6 m ² , 3 m ² , 9,0 m ² , 3 m ² , 2 m ² , 2,6 m ²
Voorfilter klasse	M klasse
Stekker	16 model , Schuko model , CEE 516 model
Zekering	16 A (traag) , 32 A (traag) , 64 A (traag)
Spanning	4200 V , 2700 V , 230 V , 400 V , 24 V DC V , 230/400 V

Vermogen	54 kW , 83 kW , 32 kW , 120 kW , 141/161 kW , 168 kW , 155/234 kW , 15/30 kW , 22/45 kW , 1/2 kW , 9 kW , 6/12/18 kW , 9/18/27 kW , 4,5/9 kW , 0,76 kW , 0,92 kW , 0,69 kW , 0,19 kW , 0,27 kW , 0,75 kW , 0,55 kW , 0,56 kW , 0,085 kW , 0,13 kW , 0,25 kW , 0,49 kW , 2700 kW , 3100 kW , 4000 kW , 3200 kW , 4200 kW , 5200 kW , 6400 kW , 0,85 kW , 1,75 kW , 1,55 kW , 0,4 kW , 1 kW , 1,1 kW , 1,2 kW , 2,4 kW , 0,75 x 2 kW , 1,8 kW , 2,2 kW , 3,3 kW , 303 kW , 1,55 kW , 1,5 kW , 3,1 kW , 4,0 kW , 5,2 kW , 6,4 kW , 4,2 kW , 2,7 kW , 3,2 kW , 2,4 kW , 0,6 kW , 0,33 kW , 0,55 kW , 0,58 kW , 0,95 kW , 0,2 kW , 0,5 kW , 0,62 kW , 3,7 kW	Optioneel
Toerental	CEE 516 Omw/min , 6800 Omw/min , 2000-7000 Omw/min , 1700-6800 Omw/min , 9500 Omw/min , 1900-9500 Omw/min , 2700-9500 Omw/min , 6600 Omw/min , 3000 Omw/min , 800-3600 Omw/min	
Werkhoogte	850 mm	
Zaaghoogte	30 mm , 0-90 mm , 0-105 mm , 135 mm , 0-135 mm , 153 mm , 145 mm , 0-145 mm , 170 mm	
Merk	Al-ko, Avola, Dust-Best, Galeski, Ghibli, Graule, Heylo, Honeywell	
Gereedschap	Slijptol	